

RESPIRATOR LOCKER®



2236 - DISPLAY WITH (3) 2250 LOCKERS AND (3) 2350 LOCKERS
2856 - DISPLAY WITH (6) 2850 LOCKERS

FEATURES

- Retail displays are perfect for high traffic areas.
- Handy supply for workers at field worksites.
- Provides each worker with hygienic storage and personal supply of respirators.
- Separate chamber stores mask during breaks.
- Allows employer to monitor respirator usage, reducing costs.
- Reduces worker time spent going to get new masks.



2236



2850



2856



BENEFITS

LET THE RETAIL DISPLAYS DO THE SELLING

The Respirator Locker® retail displays are like having an additional salesperson. Place the locker display in high traffic areas and let the display do the selling for you, while cutting out the mess of individual boxes and packaging.

HANDY TWO IN ONE STORAGE

Respirator Locker® provides hygienic storage for masks. A separate compartment permits storage of a used mask during breaks and prevents premature disposal of masks. The Respirator Locker® storage capability also allows the carbon layer in our 2850 Lockers to stay fresh, giving the user maximum comfort.

LESS WASTE AND SAVES MONEY

Reduces employee waste from taking extra masks for the day. Allows employer to monitor respirator usage. Saves time going to get fresh masks. The result is fewer respirators used and lower costs.

EASY FIT AND MORE COMFORT

Each Moldex® respirator has our exclusive Dura-Mesh® shell that protects the filter media and resists collapsing, even in heat and humidity. The 2350's exhale valve and the 2850's exclusive Ventex® valve helps reduce hot air buildup, keeping workers cooler and more comfortable. The 2850 also features a HandyStrap® that allows the mask to hang down around the users neck, so it's always ready for use.

N95 PROTECTION

NIOSH certified under 42CFR84 regulations to have a filter efficiency level of 95% against particulates free of oil up to 10x PEL. The 2850 Respirator Lockers also have a special sorbent that helps relieve workers of nuisance levels (less than OSHA PEL) of ozone and organic vapor odors. The 2350 and 2850 Lockers are suitable for most welding fumes. (It is the users responsibility to check current OSHA regulations and applicable guidelines for welding applications.)

MOLDEX TECHNICAL ASSISTANCE.

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call 800/421-0668 ext. 512/550 or email: sales@moldex.com or visit www.moldex.com.

MOLDEX
Ideas that wear well!

*Masks should be replaced in accordance with all applicable regulations.
*If used for welding, wear appropriate eye and face protection.

RESPIRATOR LOCKER®



2236 - DISPLAY WITH (3) 2250 LOCKERS AND (3) 2350 LOCKERS
2856 - DISPLAY WITH (6) 2850 LOCKERS

WARNING

Follow all instructions and warnings on the use of this respirator. Failure to do so will reduce respirator effectiveness, wearer protection and may result in sickness or death. Wear during all times of exposure.

Before use, the user must first be trained by the employer in proper respirator use in accordance with applicable safety and health standards for the contaminant and exposure level in the assigned work area.

The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.

This product has not been sold with warnings or use instructions for personnel involved in healthcare or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Dept., 800/421-0668 ext. 512/550 or 310/837-6500 ext. 512/550.

RESTRICTIONS:

1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
4. Inspect filter media and staple area prior to each use for tears and damage. Staple perforations do not effect NIOSH approval.
5. Do not alter, modify, or abuse this respirator.
6. Store unused respirators in box in a clean, dry, non-contaminated area.
7. Dispose of respirator according to your employer's policy and local regulations.
8. Dispose no later than thirty days after first use.
9. Use respirator before the "use by" expiration date printed on box or bag.
10. If used for welding, wear appropriate eye and face protection.

USE AGAINST (2236):

1. Particulate aerosols free of oil.

USE AGAINST (2856):

1. Particulate aerosols free of oil.
2. Nuisance levels (less than OSHA Permissible Exposure Limits) of Organic Vapor Odors and/or Ozone.

DO NOT USE AGAINST:

1. Concentrations of contaminants which are unknown or are immediately dangerous to life or health.
2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
3. Gases, vapors, asbestos, sandblasting, paint spray, or particulate material which generate harmful vapors. This respirator is not approved for any vapors or gases, so when used against organic vapor odors and/or ozone do not exceed the OSHA Permissible Exposure Limit.
4. Oil-based mists.

MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd.
 Culver City, CA 90232
 800/421-0668 310/837-6500
 FAX 310/837-9563

www.moldex.com e-mail: sales@moldex.com

Moldex and Respirator Locker are registered trademarks.

The mesh design is a trademark of Moldex.

U.S. Patents #D418,410, #D285,374, #D389,239, #D387,015,

5,970,585, 6,047,689, 6,076,698, 4,850,347, 5,149,468

Made in the U.S.A. 9701-718 Rev E 02/08



Printed on Recycled Paper



MOLDEX-METRIC, INCORPORATED
 CULVER CITY, CALIFORNIA, 90232 U.S.A.
 800/421-0668



THESE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS

TC-	PROTECTION ¹	RESPIRATOR			CAUTIONS AND LIMITATIONS ²
		2200N95	2300N95	2800N95	
84A-0327	N95	X			ABCJMNDP
84A-0328	N95		X		ABCJMNDP
84A-3002	N95			X	ABCJMNDP

1. Protection

N95 Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply

2. Cautions and Limitations

- A- Not for use in atmospheres containing less than 19.5 percent oxygen.
- B- Not for use in atmospheres immediately dangerous to life or health.
- C- Do not exceed maximum use concentrations established by regulatory standards.
- J- Failure to properly use and maintain this product could result in injury or death.
- M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
- N- Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configurations as specified by the manufacturer.
- O- Refer to user's instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P- NIOSH does not evaluate respirators as surgical masks.

PACKAGING

- | | |
|----------------------------------------|----------------------------------------|
| 2236 Respirator Locker® Display | 2856 Respirator Locker® Display |
| (3) 2250 Respirator Lockers and | (6) 2850 Respirator Lockers |
| (3) 2350 Respirator Lockers | (4) Masks per Locker |
| (5) Masks per Locker | (6) Lockers per Case |
| (6) Lockers per Case | |

LIMITED WARRANTY

IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

DISTRIBUTED BY:

MOLDEX®
 Ideas that wear well!

Canadian Customer Service

Tel: 310/837-6500 ext. 517

Fax: 310/837-9563