

Special Ops™

Series Earmuffs • M1 Premium Earmuff - 6109 • M2 Multi-Position Earmuff - 6209

FEATURES

- 100% PVC-Free
- Camouflage color & sleek curvy shape
- High NRR ratings
- Choose either M1 with metal band or M2 with a light weight plastic band
- M1 Premium Earmuff folds for easy storage
- M1 has a black-chrome, spring-steel band that doesn't twist out of shape like wire bands
- M2 has molded grips for easy and quick fitting.



BENEFITS

GOOD LOOKS AND STYLE

Camouflage color and sleek, curvy shape for a look that workers will want to wear.

UNIQUE METAL BAND DESIGN

The M1 Premium Earmuff features a black-chrome, spring-steel headband that resists fatigue and is more durable than wire bands. It maintains stability and doesn't twist out of shape like other wire-band earmuffs. Six different adjustment points provide a custom and comfortable fit for most head sizes. M1 folds into a super-compact size for easy storage.



QUICK AND EASY ALIGNMENT

The special molded grips of the M2 Multi-Position Earmuffs make fitting and alignment quick and easy. The cup adjustment is infinitely variable, distributing pressure evenly for a comfortable fit. The headband is made of lightweight plastic.

MOLDEX TECHNICAL SUPPORT

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information, call 800/421-0668 ext. 512/550 or 310/837-6500 ext. 512/550.

MOLDEX
Ideas that wear well!

Special Ops™

Series Earmuffs • M1 Premium Earmuff - 6109 • M2 Multi-Position Earmuff - 6209

MEAN ATTENUATION DATA OF M1 (OVER-THE-HEAD) NRR 29

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Real Ear Attenuation (dB)	16.4	23.9	27.8	36.2	37.5	43.9	46.1	44.4	42.7
Standard Deviation (dB)	2.8	2.6	2.0	3.5	2.8	3.9	3.6	4.1	4.7

TESTED ansi S3.19-1974 by Michael & Associates, Inc. State College, PA.
EPA Noise Reduction Rating 29 decibels.

MEAN ATTENUATION DATA OF M2 (OVER-THE-HEAD) NRR 26

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Real Ear Attenuation (dB)	16.4	23.9	29.4	34.2	35.6	43.7	45.0	43.2	42.1
Standard Deviation (dB)	2.3	2.5	2.3	2.4	2.4	2.4	2.1	2.8	3.1

TESTED ansi S3.19-1974 by Michael & Associates, Inc. State College, PA.
EPA Noise Reduction Rating 26 decibels.

MEAN ATTENUATION DATA OF M2 (BEHIND-THE-HEAD) NRR 24

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Real Ear Attenuation (dB)	15.3	21.6	25.2	33.1	36.1	41.4	41.3	43.5	40.9
Standard Deviation (dB)	2.4	2.4	2.2	2.4	3.2	3.8	3.4	3.4	4.3

TESTED ansi S3.19-1974 by Michael & Associates, Inc. State College, PA.
EPA Noise Reduction Rating 24 decibels.

MEAN ATTENUATION DATA OF M2 (UNDER-THE-CHIN) NRR 24

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Real Ear Attenuation (dB)	15.5	20.2	25.7	33.5	36.7	42.0	42.2	43.7	40.8
Standard Deviation (dB)	1.9	2.4	2.4	2.1	3.4	2.7	3.0	4.5	4.4

TESTED ansi S3.19-1974 by Michael & Associates, Inc. State College, PA.
EPA Noise Reduction Rating 24 decibels.

! WARNING TO USER

Use this laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn. Failure to follow all instructions could result in hearing loss or injury. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury. Earmuffs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations. Overprotection can be dangerous. The wearer must be able to hear warning signals. Wearers with hearing loss should exercise extreme caution. It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace. Failure to follow these warnings could result in serious injury or death.

PACKAGING

#6109 M1 Special Ops™ Premium Earmuff - 10 per Case
#6209 M2 Special Ops™ Multi-Position Earmuff - 20 per Case

LIMITED WARRANTY IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex, products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damage, or liability, direct, indirect, incidental, special, or consequential, arising out of sale, use, or misuse, or the inability to use products by the user.

DISTRIBUTED BY:

MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd.
Culver City, CA 90232
800/421-0668 or 310/837-6500
FAX 310/837-9563

www.moldex.com e-mail: sales@moldex.com
Moldex and SoftCoat are registered trademarks.
U.S. Patents #D459,034, #D459,033, #D464,469, #D463,857, #6,353,938.
9702-746 REV C 10/07



IN CANADA:

Pacesetter Sales & Associates
20 Arthur Hall Drive
Sharon, ON L0G 1V0
Tel: 905/478-8042
Fax: 905/478-8010
www.pacesettersales.com

MOLDEX
Ideas that wear well!