

PURA-FIT®

DISPOSABLE FOAM EARPLUGS

NRR
33
dB

6900 Pura-Fit Earplugs,
Corded



6800 Pura-Fit Earplugs,
Uncorded



FIT TO BE TRIED

Pura-Fit earplugs are tapered so they are easier to insert in any size ear canal. And they are longer too, so they are easier to grasp.

MORE COMFORT, LESS COMPLAINING

Pura-Fit is designed for increased compliance and fewer complaints. The special foam is formulated for softness and comfort, and the outer surface is smooth, so it doesn't irritate the ear canal.

NRR 33. HIGHEST INDEPENDENTLY TESTED NRR AVAILABLE

Pura-Fit is independently tested to ANSI S3.19-1974. So you know you're getting excellent protection against industrial noise.

AVAILABLE IN PLUGSTATION DISPENSER

Moldex offers the convenience, increased compliance and cost savings of our popular earplug dispenser, the PlugStation® with both Corded and Uncorded versions of the Pura-Fit foam earplugs. With the PlugStation, you can afford to put earplugs in all the places they're needed. PlugStation's convenience, ease of use, and high visibility lead to higher compliance and by giving quick access to workers. It also saves worktime.

- Compliance — High visibility to increase awareness for your hearing conservation program.
- Convenience — Hang a PlugStation anywhere plugs are needed
- Cost Savings — Workers take one pair at a time so there are no wasteful grabbing of multiple pairs.

FEATURES

- Independently tested to ANSI S3.19-1974, NRR 33dB.
- Tapered for easier insertion.
- Improved, softer foam for maximum comfort.
- Hygienically packaged in biodegradable paper pouches.
- Non-irritating, smooth surface.
- Longer length for easy fitting and removal.
- Look for the bright green color as a symbol of Moldex quality.
- 100% PVC-Free.



6844 Pura-Fit,
PlugStation
Uncorded / 250 Pairs



6845 Pura-Fit,
PlugStation
Uncorded / 500 Pairs



6882 Pura-Fit,
PlugStation
Corded / 150 Pairs



DISPOSABLE FOAM EARPLUGS

PART # / DESCRIPTION	DISPLAY	CASE
6800 Pura-Fit, Uncorded	200 Pairs/Box	10 Boxes/Case
6900 Pura-Fit, Corded	100 Pairs/Box	20 Boxes/Case
6844 Pura-Fit, PlugStation Uncorded	250 Pairs/Dispenser	6 Dispensers/Case
6845 Pura-Fit, PlugStation Uncorded	500 Pairs/Dispenser	4 Dispensers/Case
6882 Pura-Fit, PlugStation Corded	150 Pairs/Dispenser	4 Dispensers/Case

WARNING TO USER

1. Use this laboratory-derived attenuation data for comparison purposes only.
The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn.
2. Failure to follow all instructions could result in hearing loss or injury.
3. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
4. Pura-Fit earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
5. Overprotection can be dangerous. The wearer must be able to hear warning signals.
6. Wearers with hearing loss should exercise extreme caution.
7. It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace.
8. Use caution when working around machinery or other equipment to ensure neck cord does not become caught or entangled.
9. Failure to follow these warnings could result in serious injury or death.

MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 or E-mail: tech@moldex.com or visit www.moldex.com.

Keep earplugs away from infants and small children as they may get caught in the windpipe and create a choking hazard.



DISTRIBUTED BY:



MOLDEX-METRIC, INC.
10111 West Jefferson Blvd.
Culver City, CA 90232
TEL: +1 (800) 421-0668 or
+1 (310) 837-6500
FAX: +1 (310) 837-9563
E-mail: sales@moldex.com
www.moldex.com

CANADIAN CUSTOMER SERVICE
Tel: +1 (800) 421-0668, Ext. 550/512
Fax: +1 (310) 837-9563

ATTENUATION DATA

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	42.4	43.5	45.9	39.8	36.8	44.5	46.6	48.1	47.4	NRR 33	CSA AL
Standard Deviation (dB)	4.9	4.2	4.9	3.4	2.0	3.7	2.9	4.6	4.7		



Printed on Recycled Paper