

# CAMO PLUGS®

## DISPOSABLE EARPLUGS

NRR  
**33**  
dB

6609 Camo Plugs,  
Corded



6608 Camo Plugs,  
Uncorded



### SOFT COMFORTABLE FIT

Camo Plugs are made of extra-soft, extra-light foam. Their tapered shape fits easily in the ear canal and seals gently and snugly without uncomfortable pressure. They're so comfortable you'll forget you're wearing ear plugs. Good hearing is essential. When you're in and around weapons fire, aircraft, noisy vehicles or watercraft, it's important to protect it. Camo Plugs from Moldex give you the serious protection you need.

### HIGHEST INDEPENDENTLY TESTED NRR 33

Camo Plugs offer a high NRR 33 rating, making them suitable for most noisy environments. So, while they look like fun, they provide serious protection for serious users.

### AVAILABLE IN PLUGSTATION DISPENSER

Moldex offers the convenience, increased compliance and cost savings of our popular earplug dispenser, the PlugStation® with Camo Plugs foam earplugs, Uncorded. With the PlugStation, you can afford to put earplugs in all the places they're needed. PlugStation's convenience, ease of use, and high visibility lead to higher compliance and by giving quick access to workers it also saves worktime.

- Compliance — High visibility to increase awareness for your hearing conservation program.
- Convenience — Hang a PlugStation anywhere plugs are needed.
- Cost Savings — Workers take one pair at a time so there are no wasteful grabbing of multiple pairs.

### FEATURES

- Highest Independently tested NRR 33.
- Extra-soft, low-pressure foam for comfort and fit.
- Tapered shape for easy insertion and removal.
- Shaped to fit even very small ear canals.
- Non-irritating smooth surface.
- Look for the exclusive colored streaks and swirls as a symbol of Moldex quality.
- 100% PVC-Free.



6648 Camo Plugs PlugStation  
Uncorded / 500 Pairs

# CAMO PLUGS®

## DISPOSABLE EARPLUGS

PART # / DESCRIPTION	DISPLAY	CASE
6608 Camo Plugs, Uncorded	200 Pairs per Box	10 Boxes per Case
6609 Camo Plugs, Corded	100 Pairs per Box	20 Boxes per Case
6648 Camo Plugs, PlugStation	500 Pairs per Dispenser	4 Dispensers per Case

### WARNING TO USER

1. Use this laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn.
2. Failure to follow all instructions could result in hearing loss or injury.
3. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
4. Camo Plugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
5. Overprotection can be dangerous. The wearer must be able to hear warning signals.
6. Wearers with hearing loss should exercise extreme caution.
7. It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace.
8. Use caution when working around machinery or other equipment to ensure neck cord does not become caught or entangled.
9. Failure to follow these warnings could result in serious injury or death.

### MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 or E-mail: tech@moldex.com or visit www.moldex.com.

Keep earplugs away from infants and small children as they may get caught in the windpipe and create a choking hazard.



### DISTRIBUTED BY:

**MOLDEX®**  
Ideas that wear well.™

**MOLDEX-METRIC, INC.**  
10111 Jefferson Blvd.  
Culver City, CA 90232  
TEL: +1 (800) 421-0668 or  
+1 (310) 837-6500  
FAX: +1 (310) 837-9563  
E-mail: sales@moldex.com  
www.moldex.com

**CANADIAN CUSTOMER SERVICE**  
Tel: +1 (800) 421-0668, Ext. 550/510  
Fax: +1 (310) 837-9563

### ATTENUATION DATA

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	42.3	43.7	46.6	40.9	38.6	44.7	46.9	49.3	48.3	NRR 33	CSA AL
Standard Deviation (dB)	5.0	6.0	5.8	4.2	2.8	3.2	3.3	4.2	3.6		



Printed on Recycled Paper