

RESPIRATOR LOCKER®

2250P2 FIVE 2200P2 MASKS

2350P2 FIVE 2300P2 MASKS

2850P2 FOUR 2800P2 MASKS



2250P2



2350P2



2850P2



HANDY TWO IN ONE STORAGE!

Respirator Locker® provides hygienic storage for respirators. It's a personal dispenser for workers required to travel to remote locations. Fits easily in employee lockers or work vehicles. Separate compartment permits storage of a used respirator during breaks, preventing premature disposal.

LESS WASTE, SAVES MONEY

Reduces employee waste from taking extra respirators for the day. Allows employer to track respirator usage. Saves time going to get fresh respirators. The result is fewer respirators used and lower costs.

EASY FIT, MORE COMFORT

Each Moldex respirator has our exclusive Dura-Mesh® shell that protects the filter media, so it stays cleaner looking longer. The shell resists collapsing, even in heat and humidity so the respirator holds its shape longer. Model #2350P2 and #2850P2 also features an exhale valve that reduces hot air buildup. Workers stay cooler and comfortable longer. In addition Model #2850 has a special carbon layer that helps relieve workers of nuisance levels (Work Safe Exposure Standard) of ozone and organic vapour odors. Suitable for most welding fumes.

Outer Dura-Mesh keeps respirator cleaner looking

Inner Dura-Mesh helps prevent collapsing from heat and humidity

Filter is protected on both sides by Dura-Mesh

Softspun lining is comfortable against the face

FEATURES

- Allows employer to monitor respirator usage, reducing costs.
- Reduces time spent getting new respirators.
- Convenient supply for workers at field worksites.
- Provides each worker with hygienic storage and a personal supply of respirators.
- Separate chamber stores used respirator during breaks.
- Holds four or five masks per Locker.
- HandyStrap® allows mask to conveniently hang down around the user's neck when not in use.
- Locker keeps Model #2850P2 carbon layer fresh.
- Meets heat and flame resistance in accordance with AS/NZS 1716:2003 Resistance to Flame Test.
- 100% PVC-Free.



RESPIRATOR LOCKER®

2250P2 FIVE 2200P2 MASKS

2350P2 FIVE 2300P2 MASKS

2850P2 FOUR 2800P2 MASKS

PART # / DESCRIPTION	SIZE	DISPLAY	CASE
2250P2 Respirator Locker w/ 5 2200P2 Masks	M/L	5/Locker	27 Lockers
2350P2 Respirator Locker w/ 5 2300P2 Masks	M/L	5/Locker	16 Lockers
2850P2 Respirator Locker w/ 4 2800P2 Plus Nuisance OV Masks	M/L	4/Locker	16 Lockers

M/L = Medium/Large

P2 APPLICATIONS: Grinding, Torch Cutting, Sanding, Metal Pouring, Sweeping, Metal Working, Bagging, Foundries, Stone Quarrying, Agriculture, Metal Machining, Construction Sites, Cement, Ceramics Manufacturing, Underground Mining, Timber/Lumber Mills, Polishing, Buffing, Lime, Poultry, Textiles, Welding, Brazing, Soldering.

P2 Plus Nuisance Levels of Ozone and Organic Vapours Applications: Welding, Arc Cutting, Foundry Operations, Brazing, Plasma Spraying, Laser Beam Cutting/Welding, Laboratory Settings, Agriculture, Petrochemical Manufacturing, Rendering Plants, Auto Repair, Mining Operations, Waste Disposal.



USE AGAINST (2250P2, 2350P2):

1. Particulate aerosols free of oil.

USE AGAINST (2850P2):

1. Particulate aerosols free of oil.
2. Nuisance levels (Work Safe Exposure Limits) of Organic Vapor Odors and/or Ozone.

DO NOT USE AGAINST:

1. Concentrations of contaminants which are unknown, or are immediately dangerous to life or health.
2. Concentrations of particulates which exceed the maximum use concentration or 10 times the Work Safe Exposure Limit, whichever is lower.
3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors. This respirator is not approved for any vapors or gases, so when used against organic vapor odors and/or ozone do not exceed the Work Safe Exposure Limits.
4. Oil-based mists.

RESTRICTIONS

1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
4. Prior to each use, carefully inspect the entire respirator, including filter media and strap/weld attachment area for tears and damage. Staple or strap/weld attachment perforations do not affect respirator performance.
5. Do not alter, modify, or abuse this respirator.
6. Store unused respirators in box/bag in a clean, dry, non-contaminated area.
7. Dispose of respirator according to your employer's policy and local regulations.
8. Dispose no later than thirty days after first use.
9. Use respirator before the "use by" expiration date printed on box/bag.
10. If used for welding, wear appropriate eye and face protection.

WARNING TO USER

1. Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection and may result in sickness or death.
2. Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.
3. The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.
4. This product has not been sold with warnings or use instructions for personnel involved in healthcare or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Department: +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550

DISTRIBUTED BY:

MOLDEX-METRIC, INC.

10111 West Jefferson Blvd.
Culver City, CA 90232
TEL: +1 (800) 421-0668 or +1 (310) 837-6500
FAX: +1 (310) 837-9563
E-mail: sales@moldex.com www.moldex.com

AUSTRALIA

Unit 30/14-16 Stanton Road
Seven Hills, NSW 2147
TEL: +61 (02) 9838 7588 / FAX: +61 (02) 9838 7544
E-mail: moldexaustralia@moldex.com www.moldex.com

NEW ZEALAND

3 Spence Road
Henderson, Auckland, NZ
TEL: +64 (9) 837 8247 / FAX: +64 (9) 837 8248
E-mail: moldexnz@moldex.com www.moldex.com

